

Roll No.-----

Paper Code		
4	9	5
(To be filled in the OMR Sheet)		

प्रश्नपुस्तिका क्रमांक
Question Booklet No.

O.M.R. Serial No.

प्रश्नपुस्तिका सीरीज
Question Booklet Series
A

B.C.A.(Third Semester) Examination, February/March-2022
BCA-303(N)

Computer Architecture & Assembly Language

Time : 1:30 Hours

Maximum Marks-100

जब तक कहा न जाय, इस प्रश्नपुस्तिका को न खोलें

- निर्देश : —
1. परीक्षार्थी अपने अनुक्रमांक, विषय एवं प्रश्नपुस्तिका की सीरीज का विवरण यथास्थान सही- सही भरे, अन्यथा मूल्यांकन में किसी भी प्रकार की विसंगति की दशा में उसकी जिम्मेदारी स्वयं परीक्षार्थी की होगी।
 2. इस प्रश्नपुस्तिका में 100 प्रश्न हैं, जिनमें से केवल 75 प्रश्नों के उत्तर परीक्षार्थियों द्वारा दिये जाने हैं। प्रत्येक प्रश्न के चार वैकल्पिक उत्तर प्रश्न के नीचे दिये गये हैं। इन चारों में से केवल एक ही उत्तर सही है। जिस उत्तर को आप सही या सबसे उचित समझते हैं, अपने उत्तर पत्रक (O.M.R. ANSWER SHEET)में उसके अक्षर वाले वृत्त को काले या नीले बाल प्वाइंट पेन से पूरा भर दें। यदि किसी परीक्षार्थी द्वारा निर्धारित प्रश्नों से अधिक प्रश्नों के उत्तर दिये जाते हैं तो उसके द्वारा हल किये गये प्रथमतः यथा निर्दिष्ट प्रश्नोत्तरों का ही मूल्यांकन किया जायेगा।
 3. प्रत्येक प्रश्न के अंक समान हैं। आप के जितने उत्तर सही होंगे, उन्हीं के अनुसार अंक प्रदान किये जायेंगे।
 4. सभी उत्तर केवल ओ०एम०आर० उत्तर पत्रक (O.M.R. ANSWER SHEET) पर ही दिये जाने हैं। उत्तर पत्रक में निर्धारित स्थान के अलावा अन्यत्र कहीं पर दिया गया उत्तर मान्य नहीं होगा।
 5. ओ०एम०आर० उत्तर पत्रक (O.M.R. ANSWER SHEET) पर कुछ भी लिखने से पूर्व उसमें दिये गये सभी अनुदेशों को सावधानीपूर्वक पढ़ लिया जाय।
 6. परीक्षा समाप्ति के उपरान्त परीक्षार्थी कक्ष निरीक्षक को अपनी प्रश्नपुस्तिका बुकलेट एवं ओ०एम०आर० शीट पृथक-पृथक उपलब्ध कराने के बाद ही परीक्षा कक्ष से प्रस्थान करें।
 7. निगेटिव मार्किंग नहीं है।

महत्वपूर्ण : — प्रश्नपुस्तिका खोलने पर प्रथमतः जाँच कर देख लें कि प्रश्नपुस्तिका के सभी पृष्ठ भलीभाँति छपे हुए हैं। यदि प्रश्नपुस्तिका में कोई कमी हो, तो कक्ष निरीक्षक को दिखाकर उसी सीरीज की दूसरी प्रश्नपुस्तिका प्राप्त कर लें।

Rough Work / रफ कार्य

1. According to Von Neumann architecture, for computer_____ is/are stored in main memory.
 - (A) Data only
 - (B) Programs only
 - (C) Data and programs
 - (D) None of the above
2. The extremely fast, small RAM are called as :
 - (A) Heap
 - (B) Cache
 - (C) Stack
 - (D) Accumulator
3. The ALU uses_____ to store the intermediate results.
 - (A) Register
 - (B) RAM
 - (C) Accumulator
 - (D) Stack
4. The I/O interface required to connect the I/O device to the bus has :
 - (A) Address decodes, register, control circuit
 - (B) Control circuit and register
 - (C) Register only
 - (D) Control circuit only
5. The main use of single bus structure is :
 - (A) Cost effective connectivity and speed
 - (B) Cost effective connectivity and ease of attaching
 - (C) Fast data transfer
 - (D) None of the above

6. Instruction (for decoding) is stored in :
 - (A) PC
 - (B) Register
 - (C) IR
 - (D) MAR
7. During the instruction cycle for execution of an instruction, which register gets initialized first :
 - (A) MDR
 - (B) PC
 - (C) IR
 - (D) MAR
8. A processor performing fetch or decode of different instructions during the execution of another instruction is called :
 - (A) Pipelining
 - (B) Superscalar
 - (C) Array Processor
 - (D) Vector Processor
9. When doing repetitive task through Loop operation, the instructions are stored in _____ for efficiency.
 - (A) Register
 - (B) Cache
 - (C) Heap
 - (D) Stack
10. CISC stands for :
 - (A) Complete instruction set computer
 - (B) Complex instruction set computer
 - (C) Complex instruction sequence computer
 - (D) Computer for integrated set computer

11. To Reduce speed mismatch between CPU registers and main memory,_____ is used.
- (A) Heap
 - (B) Stack
 - (C) Cache
 - (D) High capacity RAM
12. Find the correct statement about zero address instruction :
- (A) Stack pointer given the effective address
 - (B) There is no operand in the instruction
 - (C) Effective address is zero
 - (D) None of the above
13. The addressing mode using the extra indirection pointer is called _____ addressing mode.
- (A) Relative
 - (B) Indexed
 - (C) Register
 - (D) Indirect
14. The addressing mode, which uses program counter and other info for effective address calculation is_____ addressing mode.
- (A) Relative
 - (B) Direct
 - (C) Auto increment
 - (D) Implied
15. The Addressing mode where the operand value is part of instruction is _____ addressing mode.
- (A) Direct
 - (B) Immediate
 - (C) Relative
 - (D) Indirect

16. A 16 bit address generates an address space of _____ locations.
- (A) 16 K
 - (B) 64 K
 - (C) 4096
 - (D) 1024
17. If a system is 32 bit machine, then the length of each word is :
- (A) 4 byte
 - (B) 8 byte
 - (C) 12 byte
 - (D) 16 bit
18. The type of memory assignment used in Intel Processor is _____.
- (A) Big Endian
 - (B) Little Endian
 - (C) Medium Endian
 - (D) Small Endian
19. Which is true about LDA instruction (in 8085) ?
- (A) Loads the content of Hard disk into a memory loc
 - (B) Loads the content of top of stack into accumulator
 - (C) Loads the content of memory location to accumulator
 - (D) Loads the content of memory to stack
20. The transfer of bulk of data is done (between memory and peripheral) by :
- (A) Microcontroller
 - (B) DMA controller
 - (C) Arbitrator
 - (D) I/O processor

21. In a system which has 16 registers to do data processing, _____ bits are used to recognize the specified register.
- (A) 16
 - (B) 12
 - (C) 4
 - (D) 6
22. The steps in instruction cycle in proper order is :
- (A) Fetch, decode, storage, execute
 - (B) Fetch, storage, decode, execute
 - (C) Fetch, decode, execute, storage
 - (D) Fetch, storage, execute
23. When using branch instruction, the content of which register is altered first ?
- (A) Instruction register
 - (B) Data register
 - (C) Program counter
 - (D) Accumulator
24. The condition Flag Z is set to 1 indicate :
- (A) Error in the operation
 - (B) Result is zero
 - (C) There is an error resulted
 - (D) Interrupt arise
25. _____ converts the program written in assembly language to m/c language.
- (A) Assembling
 - (B) Assembler
 - (C) Interpreter
 - (D) Compiler

26. Micro operation is _____.
- (A) Complex operation on register
 - (B) Elementary operations done on register
 - (C) Complex instruction taking multiple clock cycles
 - (D) None of the above
27. The return address of the subroutine is pointer to by :
- (A) Program counter value stored on stack
 - (B) Subroutine register
 - (C) Memory address register
 - (D) Stack pointer
28. The place from which the return address is generated and used is :
- (A) Stack
 - (B) RAM
 - (C) Heap
 - (D) ROM
29. The microprocessor notifies a Read or Write operation by :
- (A) Raising an interrupt signal
 - (B) Sending special control signal along BUS
 - (C) Enabling read/write bits of the device
 - (D) Adding extra bit to address
30. To check the readiness of the slower I/O device, the processor use :
- (A) Buffer register
 - (B) Status flag
 - (C) Interrupt
 - (D) Exception

31. The mode of Data transfer, which offer high speed I/O Transfer is :
- (A) Programmed I/O
 - (B) Interrupt driven I/O
 - (C) Interrupt
 - (D) DMA
32. The Signal sent from processor to device after receiving an interrupt is :
- (A) Service signal
 - (B) Return signal
 - (C) Interrupt
 - (D) Interrupt acknowledgement
33. After the Interrupt service routine is returned _____ should be loaded again.
- (A) Register contents
 - (B) Register contents and flag condition
 - (C) Flag condition
 - (D) Stack content
34. Interrupts initiated by an instruction is called :
- (A) Internal interrupt
 - (B) External interrupt
 - (C) Hardware interrupt
 - (D) Software interrupt
35. The DMA transfer is initiated by :
- (A) Operating system
 - (B) DMA controller
 - (C) Processor
 - (D) I/O device

36. In DMA Transfer, the required signals and addresses are given by_____.
- (A) Processor
 - (B) Interrupt service routine
 - (C) DMA controller
 - (D) The program
37. If an interrupt is caused by an instruction attempting to divide by zero, is said to create_____.
- (A) External interrupt
 - (B) Internal interrupt
 - (C) Priority interrupt
 - (D) Software interrupt
38. In Booth's algorithm implementation, for multiplication of data represented with 2's complement form, What type of shift right operation is used :
- (A) Logical
 - (B) Arithmetic
 - (C) Rotation with carry
 - (D) Circular
39. Which of the following memory unit communicates directly with CPU ?
- (A) Secondary memory
 - (B) RAM
 - (C) Auxiliary memory
 - (D) None of the above
40. Which of the following informs a computer to perform a particular task ?
- (A) Accumulator
 - (B) Instruction code
 - (C) Register
 - (D) Stack

41. What does SIMD stand for :
- (A) Same instruction multiple data
 - (B) Simple instruction memory device
 - (C) Single instruction multiple data
 - (D) Single instruction multiple device
42. Which of the following is not a status bit :
- (A) Unsigned bit
 - (B) Signed bit
 - (C) Carry bit
 - (D) Zero bit
43. Which is not True about program counter ?
- (A) It is an instruction pointer
 - (B) It counts the statements in a program
 - (C) It has to be initialized first at the start of instruction cycle
 - (D) It stores the address of the next instruction to be executed
44. What does stack pointer hold ?
- (A) Address of current instruction
 - (B) Address of current data
 - (C) Address of next instruction
 - (D) Address of top element of stack
45. A system with an n-bit microprocessor has :
- (A) n-bit data bus
 - (B) n-bit address bus
 - (C) n-bit program counter
 - (D) n-bit stack pointer

46. Which of the following is an elementary operation executed on data stored in register ?
- (A) Macro operation
 - (B) Micro operation
 - (C) Stack operation
 - (D) Parallel operation
47. Computer bus consists of _____.
- (A) Accumulator
 - (B) Group of parallel lines
 - (C) Register
 - (D) Decodes
48. A single bus system for data transfer between 8 register each of 16 bit, the number of multiplexers and size of each multiplexer are _____ respectively.
- (A) 16, 8×1
 - (B) 8, 16×1
 - (C) 16, 16×1
 - (D) 8, 8×1
49. Which of the following circuit has 2^n input lines and a single output lines ?
- (A) Multiplexer
 - (B) Decodes
 - (C) Demultiplexer
 - (D) Encoder
50. Which of the following register collects the result of computation ?
- (A) Instruction register
 - (B) Storage register
 - (C) MDR
 - (D) Accumulator

51. Which of the following is a function of control unit :
- (A) It performs logic operation
 - (B) It performs arithmetic operation
 - (C) It stores program
 - (D) It decodes the instructions of the program
52. Which is not true about RISC ?
- (A) It stands for reduced instruction set computer
 - (B) It uses microprogrammed control unit
 - (C) Memory access is limited to load and store instruction
 - (D) Easily decoded instruction format
53. For arithmetic pipeline (for add/ subtract), the following one the segments :
- (i) Align the mantissa
 - (ii) Add/ subtract mantissa
 - (iii) Compare exponent
 - (iv) Normalize result
- (A) (i), (ii), (iii), (iv)
 - (B) (iii), (i), (ii), (iv)
 - (C) (ii), (i), (iii), (iv)
 - (D) (iii), (ii), (i), (iv)
54. Which of the following is a bulk data Transfer Technique ?
- (A) Interrupt driven I/O
 - (B) DMA
 - (C) MIMD
 - (D) Subroutine call
55. The 8085 MP has :
- (A) 8 bit data bus, 8 bit address bus
 - (B) 8 bit data bus, 16 bit address bus
 - (C) 16 bit data bus, 8 bit address bus
 - (D) 16 bit data bus, 8 bit data bus

56. Highest priority interrupt in 8085 is :
- (A) RST 7.5
 - (B) RST 6.5
 - (C) TRAP
 - (D) INTR
57. In 8085 microprocessor, which signal is used to delay Read, Write until a slow responding peripheral is ready to send or accept data :
- (A) ALE
 - (B) READY
 - (C) HOLD
 - (D) INTR
58. When 8085 performs the operation 7AH - A2H what will be the outcomes :
- (A) Result = D8H, Cy =1, S= 0
 - (B) Result = D8H, Cy =0, S= 1
 - (C) Result = D8H, Cy =1, S= 1
 - (D) Result = D8H, Cy =0, S= 0
59. In 8085 microprocessor, what is size of stack pointer (SP) :
- (A) 6 bit
 - (B) 16 bit
 - (C) 8 bit
 - (D) 32 bit
60. Which of the following is used to store important info during subroutine call and interrupt ?
- (A) Data register
 - (B) Queue
 - (C) Stack
 - (D) Address register

61. Which of the following is not a control signal in 8085 ?
- (A) Read
 - (B) Write
 - (C) Reset
 - (D) ALE
62. The no of general purpose programmable register and memory pointer register are _____ , _____ respectively.
- (A) 7, 2
 - (B) 8, 4
 - (C) 10, 2
 - (D) 8, 2
63. ALE stands for (in 8085) :
- (A) Address lower end
 - (B) Address latch end
 - (C) Address lower enable
 - (D) Address latch enable
64. Which control signal is used for demultiplexing lower order address and data bus ?
- (A) ALE
 - (B) HOLD
 - (C) RD
 - (D) IO/\bar{M}
65. Which signal causes the microprocessor to terminate current activity ?
- (A) Interrupt
 - (B) Reset
 - (C) Both
 - (D) HOLD

66. Which of the following Pins of 8085 are used for DMA transfer_____?
- (A) HOLD, HLDA
 - (B) INTR, IN
 - (C) RD, WR
 - (D) ALE, IO/ \bar{M}
67. The flag register in 8085 has_____ no. of flag bits.
- (A) 4
 - (B) 5
 - (C) 6
 - (D) 3
68. The content of accumulator after the execution of following instruction will be :
- MVI A, L8 H
ORA A
RAL
- (A) 6E H
 - (B) 91 H
 - (C) EF H
 - (D) ED H
69. For the following code, find the final value of Accumulator
- MVI A, 33H
MVI B, 78H
ADD B
CMA
ANI 52H
- (A) 01 H
 - (B) 11 H
 - (C) 50 H
 - (D) 32 H

70. In the following instruction :

LXI H, 2050

MVI A, 20H

SUB M,

The size of each instruction written above are _____ respectively.

(A) 3, 2, 3 bytes

(B) 3, 2, 2 bytes

(C) 3, 2, 1 bytes

(D) 2, 1, 3 bytes

71. The CPI instruction :

(A) Compare Accumulator content and data byte

(B) Compare Accumulator and register

(C) Complement data bytes

(D) Complement accumulator

72. ADD M instruction uses _____ addressing mode.

(A) Register indirect

(B) Memory

(C) Direct

(D) Register

73. What is not a possible register pair used in 8085 ?

(A) Accumulator and flag register

(B) Accumulator and B register

(C) Register D and E

(D) Register H and L

74. Input-output interface is used for :

(A) Signal conversion only

(B) Synchronization only

(C) Signal, data conversion, synchronization

(D) Data processing

75. Hand shaking method :
- (A) Used for synchronizing independent units communicating
 - (B) Uses strobe pulse
 - (C) Does not guarantee the receipt of message
 - (D) Used for data conversion
76. Software method for implementing priority interrupt is called _____.
- (A) Daily chaining
 - (B) DMA
 - (C) Polling
 - (D) Priority encoder
77. Accumulator is a type of :
- (A) Cache
 - (B) RAM
 - (C) MAR
 - (D) Register
78. Choose the correct statement :
- (A) Read and write control lines in CPU are bidirectional
 - (B) Read and write control lines in DMA controller are bidirectional
 - (C) Read, write control lines are unidirectional in DMA controller
 - (D) None of the above
79. Which is not true for a super computer ?
- (A) It is commercial computer with vector instar and pipeline floating point arithmetic operation
 - (B) It is suitable as a general purpose computer
 - (C) It is very costly
 - (D) First super computer is CRAY-1

80. Which is not true about array processor ?
- (A) It is a MIMD organized processor
 - (B) It can be attached to host computer
 - (C) It can be organized with multiple processing elements and multiple local memories
 - (D) These are highly specialized processor
81. Which modes give easiest way to find operand ?
- (A) implied, direct
 - (B) Implied, immediate
 - (C) Register indirect, relative
 - (D) Indexed, relative
82. In register mode, to specify any of 8 register, the no. of bits of used to specify a register is :
- (A) 2
 - (B) 3
 - (C) 8
 - (D) 4
83. In which of the following form, the computer stores data/instruction in memory ?
- (A) Binary
 - (B) Hexadecimal
 - (C) Octal
 - (D) Decimal
84. For program execution by the computer, the data and instructions are stored temporarily in :
- (A) ROM
 - (B) RAM
 - (C) Control Unit
 - (D) Hard disk

85. Which is true about data transfer instructions in 8085 ?
- (A) They set all flags
 - (B) They do not affect any flags
 - (C) They do not affect source content
 - (D) In 08 H is a data transfer instruction
86. Which one is false ?
- (A) INR and DCR affect content of given register
 - (B) INR and DCR affect all flags
 - (C) ADD, SUB instruction assume Accumulator as implied operand
 - (D) ADD, SUB do not affect the content of operand register
87. JZ, JNZ instructions are used to :
- (A) Check the end of loop execution
 - (B) Unconditionally jump
 - (C) execute based on carry flag
 - (D) None of the above
88. Which of the following is an instruction for Data Transfer from memory (pointed by H1pair) to microprocessor ?
- (A) MOV M, R
 - (B) MOV R, M
 - (C) MVI R, M
 - (D) MVI M, R
89. INX B means :
- (A) Increment register B
 - (B) Increment register pair BC
 - (C) Increment is register pair BD
 - (D) Increment is in Register mode

90. RLC and RRC instructions means rotate accumulator :
- (A) Left with carry, right with carry
 - (B) Left, right
 - (C) Right, left
 - (D) None of the above
91. Compare and complement opcodes in 8085 are _____ and _____ respectively.
- (A) CMP, CMA
 - (B) CMA, CMP
 - (C) CM, CMA
 - (D) CP, CMA
92. Which statement is true about LXI H, 2080 instech :
- (A) Load H, L register with 20H, 80H respectively
 - (B) Load H, L register with 80H, 20H respectively
 - (C) It is a 2-byte instruction
 - (D) It uses direct addressing mode
93. Among 5 interrupts of 8085 :
- (A) TRAP is maskable interrupt
 - (B) TRAP is non-maskable interrupt & highest priority
 - (C) TRAP is having lowest priority
 - (D) None of the answer is correct

94. About PUSH and POP instruction in 8085, which is True :
- (A) They are data transfer instructions
 - (B) They are two byte instruction
 - (C) They use top most memory location of stack
 - (D) They affect all flags
95. Which of following is true about CALL and RET instruction :
- (A) Both are 3 byte instruction
 - (B) Both uses Push and POP operations respectively for their implementation
 - (C) Both transfer control conditionally
 - (D) None of the above
96. Which of the following circuit is part of RAM and ROM ?
- (A) Address decodes
 - (B) Encodes
 - (C) Multiplexer
 - (D) Demultiplexer
97. Which of the following circuit is used to add 3 bits of data including a carry ?
- (A) Half adder
 - (B) Full adder
 - (C) Encoder
 - (D) Register

98. What components are used in BUS design or data transfer between registers in CUP?
- (A) MUX, decoder
 - (B) MUX, encoder
 - (C) MUX, adder
 - (D) DEMUX, decoder
99. Subtraction in intel 8085 is carried by :
- (A) 2's complement
 - (B) 1's complement
 - (C) 9's complement
 - (D) Sign magnitude
100. Collection of 8 bits is called :
- (A) Nibble
 - (B) Word
 - (C) Byte
 - (D) Structure

DO NOT OPEN THE QUESTION BOOKLET UNTIL ASKED TO DO SO

1. Examinee should enter his / her roll number, subject and Question Booklet Series correctly in the O.M.R. sheet, the examinee will be responsible for the error he / she has made.
 2. **This Question Booklet contains 100 questions, out of which only 75 Question are to be Answered by the examinee. Every question has 4 options and only one of them is correct. The answer which seems correct to you, darken that option number in your Answer Booklet (O.M.R ANSWER SHEET) completely with black or blue ball point pen. If any examinee will mark more than one answer of a particular question, then the first most option will be considered valid.**
 3. Every question has same marks. Every question you attempt correctly, marks will be given according to that.
 4. Every answer should be marked only on Answer Booklet (O.M.R ANSWER SHEET). Answer marked anywhere else other than the determined place will not be considered valid.
 5. Please read all the instructions carefully before attempting anything on Answer Booklet (O.M.R ANSWER SHEET).
 6. After completion of examination please hand over the Answer Booklet (O.M.R ANSWER SHEET) to the Examiner before leaving the examination room.
 7. There is no negative marking.
- Note:** On opening the question booklet, first check that all the pages of the question booklet are printed properly in case there is an issue please ask the examiner to change the booklet of same series and get another one.